



INOX[®]

PIGMENTS

Add Colours Add Values



RAL SHADE ALSO AVAILABLE



RAL SHADE ALSO AVAILABLE



Purple Tone White IP 116



Sera Pink IP 913



Italian Ivory IP 703



Light Green IP 421



Salwan Gray IP 306



Light Pastel Blue IP 503



Lemon Yellow IP 601



Botochino IP 912



Green Tone White IP 117



Int. Orange IP 208



Red Oxide IP 206



Pastel Green IP 401



Pale Gray IP 305



Pastel Blue IP 502



Golden Yellow IP 602



Sand Stone IP 118



Ivory IP 700



Light Orange IP 212



Magenta Red IP 204



Parrot Green IP 403



Stone Gray IP 310



Nile Blue IP 514



Traffic Yellow IP 603



Golden Brown IP 800



D K Ivory IP 705



Deep Orange IP 210



Crimson IP 904



Apple Green IP 404



Traffic Gray IP 316



Smock Gray IP 307



Buma Brown IP 803



Roman Brown IP 801



Royal Ivory IP 701



Signal Red IP 202



Purple IP 907



Mint Green IP 412



Satlij Gray IP 311



Alpine Blue IP 510



Beige IP 708



Mahogany IP 906



Dark Mushroom IP 219



P O Red IP 201



Olive Green IP 411



Leaf Green IP 415



Dark Gray IP 324



Oxford Blue IP 506



Dyna IP 720



Chocolate Brown IP 802

★ Base white, New White, B.T. White, Black and Transparent Shades (Blue-Red-Brown-Yellow-Green) are also available.
★ We also manufacture Pigment as per RAL Shade Code, Metallic Pigment & Lead free Pigments.

★ Our Pigment also compatible with Epoxy Resin.
★ We also supply Pre Pigmented Gel coat as per order / specification.

SALIENT FEATURES:

1. Suitable for Composite/SMC/DMC/FRP/Pultrusion/Epoxy Industries.
2. Easy Dispersion.
3. Good Coverage and Opacity.
4. Produces excellent gloss finish
5. Good Light Fastness.
6. Excellent Weatherability Properties.
7. Available in wide range.
8. Batch to Batch consistency.
9. All Pigments test by Spectrophotometer to ensure batch by batch consistency.

DIRECTIONS FOR USE:

1. Remove the sealed plastic cover and stir the paste before use.
2. Add Pigment in Resin or Gelcoat for desired colours.
3. For Economical coverage, apply first coat slow and less, second fast with full coverage.
4. Use 6% to 10% Pigment paste for FRP moulding and 3 to 5% or less as per requirement in DMC/SMC or other usage.
5. Use separate spatula (spoon) for different colour.
6. Replace the plastic lid after use for storage and shelf life.

PROPERTIES

It is supplied at a viscosity compatible for FRP/DMC/SMC Moulding materials forming a smooth film, free from brush marks with durability and resistance to atmosphere.

PACKAGING:

Plastic Container: 100gm & 1 Kg

HDPE Bucket: 5 Kgs | 10Kgs | 25 Kgs



Company Stock Outlet

DELHI | KOLKATA | MUMBAI | BENGALURU | GURUGRAM | BHIWADI | NOIDA | BARODA | PUNE

Dealers

FARIDABAD | GHAZIABAD | DELHI | KANPUR | LUCKNOW | JAIPUR | UDAIPUR | BIKANER | LUDHIANA | CHANDIGARH
VADODRA | KOLKATA | INDORE | MUMBAI | PUNE | NASHIK | BENGALURU | CHENNAI | HOSUR | KERALA | KATHMANDU (NEPAL)

Mobile: +91-8130087303 | **E-mail:** inoxpigments@gmail.com | **Website:** www.innovativeresins.in